



- Provides 6 antenna Ports in a slim-line form factor
- Optimized Azimuth patterns for Min Inter-Sector Interference
- Industry leading Minimal Wind-Load design

- 700, 850, PCS, AWS & WCS bands in one antenna
- AISG & 3GPP compliant internal (RET) with Smart Bias T

The Quintel MultiServ™ Multiband 6 Port Antenna with patented QTilt™ technology uniquely delivers three independent services in a single slim-line antenna. This enables existing antenna network sites to be upgraded constraint free to add new services such as LTE for 700, 850, PCS, AWS and WCS bands with the replacement of one antenna. The QS8656-5 also provides 4x1695-2400MHz ports as two side-by-side (CLA-2X) arrays for connection to 2T4R/4T4R services.

Electrical Characteristics	2x Ports 1&2		4x Ports 3 - 6			
Operating Frequency (MHz)	698-894		1695-2400			
	698-806	814-894	1695-1780	1850-1990	2110-2180	2300-2400
Azimuth beamwidth ¹	63°	60°	68°	66°	61°	59°
Elevation beamwidth ¹	10.0°	8.5°	6.3°	5.9°	5.3°	4.9°
Gain ¹ (dBi)	14.5	14.8	17.3	17.2	17.9	17.7
Polarization	±45°		±45°			
Electrical down-tilt range	2°-10°		0° – 8°			
Upper SLL (20° > mainbeam) ¹	-17dB	-16dB	-15dB	-14dB	-14dB	-13dB
Front to Back Ratio(180°±10°) ¹	≥25dB	≥25dB	≥29dB	≥29dB	≥32dB	≥30dB
Port to Port isolation ¹	≥32dB	≥29dB	≥30dB	≥30dB	≥30dB	≥30dB
Return loss (VSWR)	14dB(1.5)	14dB(1.5)	14dB(1.5)	14dB(1.5)	14dB (1.5)	14dB(1.5)
X Polar Discrimination (at 0°)	>17dB	>16dB	>24dB	>20dB	>16dB	>16dB
Max Power handling (per any port)	500 watts		250 watts			
Total Composite Power (all ports)	1750 watts					
PIM (3 rd Order) (2x43dBm)	>153dBc		>153dBc			

¹ Typical Performance across frequency and Downtilt.



Mechanical Characteristics

Dimensions	L 96"(2438mm) x W 12"(304mm) x D 9.6"(245mm)
Weight (excl mounting brackets)	84lbs (38kg)
No. of Connectors	6x 7/16 DIN Female Long Neck
Max Wind Speed	150mph (67m/s)
Equivalent Projected Area ²	Front: 3.2ft ² (0.30m ²) Side: 6.1ft ² (0.57m ²)
Wind Load ² @ 160km/h (45m/s)	Front: 352N (79.2 lbs), Side: 680N (153 lbs)
Operating Temperature	-40°C to +65°C

Fully Integrated

- AISG Standalone
- Factory Default
- Surge Immune
- Device Type
- AISG Data
- No of connectors
- Connector
- MTBF



(AISG PIN)

es



RET Configuration

The Quintel MultiServ™ Multiband 6 Port Antenna has the following Array, RF Port and AISG I/O Configurations.

The 6-Port array topology consists of 3 radiating arrays:


R1 – 698-894MHz
Y1 – 1695-2400MHz
Y2 – 1695-2400MHz

RF Connector Port Configuration

	Ports	Freq (MHz)
R1	i-2	698-787
Y1	i-4	1695-2400
Y2	i-6	1695-2400



The RET Devices can be communicated with either via the designated external AISG connector or RF Port as shown below.



AISG I/O Configuration

RET Device	Band	RF Ports
2	1695-2400	3-6

AISG I/O Configuration

RET Device	Band	RF Ports
1	698-894	1-2

Multiband Optimization

The Quintel MultiServ™ Multiband 6 Port Antenna is an ideal solution for independently optimizing multiple services when rapidly introducing new technologies. Technology agnostic, each pair of ports provides flexibility for existing and future technologies such as CDMA/EVDO, GSM/EDGE, UMTS/HSPA, and LTE and advanced 2T4R and 4T4R MIMO implementations at high-bands.

The tilt of each service is controlled independently via internal RET actuators compliant to AISG1.1, AISG2.0 and 3GPP protocols. The QS8656-5 provides a total of 2 independent tilts:

- 1x(698-894MHz)
- 1x Left & Right Array (1695-2400MHz)

Design Optimization

All Quintel antennas use the same mechanical mounting brackets thus making maintenance swaps easy and future proof. All Quintel Antennas also have Azimuth patterns optimized with network design and deployment in mind. The 3dB Azimuth beamwidth is ~65° as with most Antennas, but we have optimized how the pattern rolls-off and where the sidelobes emerge such that there is minimal Inter-Sector Interference when 3x sectors are deployed. For interference limited networks, we can deliver 25% more capacity.

About Quintel

Quintel is a leading innovator in the design, development, and delivery of network-efficient antenna solutions for wireless operators worldwide. The company's products enable global wireless operators to independently deploy and optimize multiple air interfaces or services on a single standard antenna platform. Quintel is the only antenna maker whose products can increase a wireless network's capacity and provide additional services, without increasing the number or size of antennas. Quintel is headquartered in Rochester, New York with additional offices throughout North America and Europe. More information about Quintel is available at www.quintelsolutions.com.

Tel (Americas): +1 (585) 420-8720
info@quintelsolutions.com

THIS DOCUMENT PROVIDES A GENERAL DESCRIPTION OF THE PRODUCT AND SHALL NOT FORM PART OF ANY CONTRACT.

© 2019 Quintel Technology Limited. All rights reserved. Quintel and the Quintel logo are registered trademarks Quintel Technology Limited. All other trademarks are the property of their respective owners.