



- Designed for supporting 4T4R Radios at Low-Band & Mid-Band
- Optimized Azimuth patterns for Min Inter-Sector Interference
- Industry leading Minimal Wind-Load Radome design

- Full length Low & Mid-band Arrays for optimal VBW & Gain
- Best in class Quality and Internal PIM performance
- Designed to minimize External PIM

Electrical Characteristics	4x Ports 1 2 3 4		4x Ports 5 6 7 8			
	698-894		1695-2400			
Operating Frequency (MHz)	698-803	824-894	1695-1780	1850-1990	2110-2180	2300-2400
Peak Gain (dBi)	15.0	15.8	17.0	17.5	17.8	18.4
Azimuth beamwidth ¹	73°	68°	65°	66°	61°	60°
Elevation beamwidth ¹	9.2°	8.3°	6.4°	5.8°	5.3°	4.8°
Gain ¹ (dBi)	14.1	15.0	16.2	16.8	17.2	17.8
Polarization	2x ±45°		2x ±45°			
Electrical down-tilt range	2°-12°		0°-9°			
USLS 20°>mainbeam (dB)	>12	>12	>18	>18	>17	>16
FTB at 180°±10° (dB) ¹	25	29	31	31	34	33
Port to Port isolation ¹	25	25	25	25	25	25
Return loss/VSWR (dB)	14/1.5	14/1.5	14/1.5	14/1.5	14/1.5	14/1.5
X Polar at 0° (dB)	15	15	18	15	18	18
Max Power handling (port)	300 Watts		250 Watts			
Max Power (all ports)	1100 Watts					
PIM (dBc: 2x43dBm)	>153		>153			

¹ Typical Performance across ports, frequencies and Downtilt.

Mechanical Characteristics


Dimensions	L 96"(2438mm) x W 18.1"(460mm) x D 9.6"(245mm)
Weight (excl mounting brackets)	104lbs (47.2kg)
No. of Connectors	8x 4.3-10.0 DIN Female Long Neck
Max Wind Speed	150mph (67m/s)
Equivalent Projected Area ²	Front: 3.38ft ² (0.31m ²) Side: 1.71 ft ² (0.16m ²)
Wind Load ² @ 161km/h (45m/s)	Front: 186lbs (827N), Side: 94lbs (418N)
Operating Temperature	-40°C to +65°C

² Equivalent Projected Area and Wind Load derived from simulation measurements.
Equivalent Projected Area assumed C_d=1



Tel: +1 (585) 420-8720
info@quintelsolutions.com
www.quintelsolutions.com

THIS DOCUMENT PROVIDES A GENERAL DESCRIPTION OF THE PRODUCT AND SHALL NOT FORM PART OF ANY CONTRACT.
© 2020 Quintel USA, Inc. All rights reserved. Quintel and the Quintel logo are registered trademarks Quintel Cayman Limited.



- Designed for supporting 4T4R Radios at Low-Band & Mid-Band
- Optimized Azimuth patterns for Min Inter-Sector Interference
- Industry leading Minimal Wind-Load Radome design

- Full length Low & High-band Arrays for optimal VBW and Gain
- Best in class Quality and Internal PIM performance
- Designed to minimize External PIM

Fully Integrated RET Characteristics

Protocol	V 1.1/2.0/3GPP (SRET Type 1)
Surge immunity	IEC 61000-4-5:2005 4KV(AISG PIN)
AISG Data rate	9.6 kbps
RET Connectors	1x 8-Pin DIN Female & 1x 8-Pin DIN Male

Port Layout, Array Configuration and RET ID



Left Left Right Right



RET ID	Ports		Arrays		Freq Range	
1	1	2	R1		698-894MHz	
2			3	4	R2	698-894MHz
3	5	6	Y1		1695-2400MHz	
4			7	8	Y2	1695-2400MHz

Tel: +1 (585) 420-8720
info@quintelsolutions.com
www.quintelsolutions.com

THIS DOCUMENT PROVIDES A GENERAL DESCRIPTION OF THE PRODUCT AND SHALL NOT FORM PART OF ANY CONTRACT.
© 2020 Quintel USA, Inc. All rights reserved. Quintel and the Quintel logo are registered trademarks Quintel Cayman Limited.